









# SPRAY HEAT SUPER - FERRARI RED TEXTURED

Technical Data Sheet No 834

	General Technical Description	Surface	Pretreatment / Cleaning of substrate
VOC compliant with the regulations	2-3 passes	For the painting of metal objects which are exposed to temperatures of up to 300°C (572°F)	 Clean substrate using a soft cloth and BODY 770 ANTISIL NORMAL / BODY 771 ANTISIL FAST
Silicone Aerosol Paint	Dust free 10 min at 23°C (73°F)		 Make sure you always use appropriate face protection and good ventilation
Recommended for the painting of objects which are exposed to temperatures of up to 300°C (572°F)			Make sure the surface is first wiped dry and then air dried.
Excellent results			

**Product Application:** »» Apply on objects which are exposed to temperatures up to 300°C (572°F). Apply two to three medium coats necessary to cover the area waiting 5-10 min in between each coat. Each coat should appear uniform and dry before the next one is applied.

 Shake well before using	<b>Flash Point:</b> -97°C (-142.6°F)	<b>Remarks:</b> <ul style="list-style-type: none"> <li>• Always try to use the product in accordance with the specifications provided.</li> <li>• It can be used by countries that do not adopt the VOC legislation as well.</li> <li>• Shake thoroughly before use.</li> <li>• Optimum operating temperature range 10-25°C (50-77°F).</li> </ul>	<b>Storage shelf life:</b> Store in a cool place and use within 36 months for best results. +5 to +25°C (41-77°F).
 2-3 coats approximately 20-30 microns (0.78-1.2 mil)	<b>Specific Gravity:</b> 0.89 g/cm <sup>3</sup>		
 Dust free 10 min at 23°C (73°F)	<b>Solid Content (No thinner):</b> 14% Weight		
 Full hardness within 24 hours Heat for 30-60 min at 160-200°C (320-392 °F) to achieve hardening	<b>VOC (2001/42/EC)</b> This product is an aerosol product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 770g/L. 2004/42/II(b)(840)770		
	<b>Theoretical Coverage:</b> -		
	<b>Cleaning of equipment:</b> -		

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 4/2017, October 2017