



Auto Refinishing Products

Page 1/19

Printing date 25.04.2020

Revision: 25.04.2020

Version number 39

Safety Data Sheet
in accordance with HSNO

* **SECTION 1: Identification of the substance or mixture and of the supplier**

· **1.1 Product identifier**

· **Trade name:** **BODY BUMPER PAINT SPRAY**

· **Article number:** 591

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· **Environmental release category** ERC2 Formulation into mixture

· **Article category** AC1 Vehicles

· **Application of the substance / the mixture**

Coating compound/ Surface coating/ paint

Surface protection

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· **Further information obtainable from:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

NZ
(Contd. on page 2)

Trade name: **BODY BUMPER PAINT SPRAY**

(Contd. of page 1)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

Muta. 1A H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Acute Tox. 5 H333 May be harmful if inhaled.

Additional information:

6.1E Substances that are acutely toxic – May be harmful, aspiration hazard

6.3A Substances that are irritating to the skin

2.1.2A Flammable aerosol

6.9 (Narcotic) Substances that are harmful to human target organs or systems

6.6A Substances that are known or presumed human mutagens

6.7A Substances that are known or presumed human carcinogens

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Signal word Danger

Hazard-determining components of labelling:

butane, pure

xylene

isobutane

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

(Contd. on page 3)

Trade name: **BODY BUMPER PAINT SPRAY**

(Contd. of page 2)

- P251 Pressurized container: Do not pierce or burn, even after use.
- P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

















- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/Information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of hazardous substances

· **Dangerous components:**

CAS: 106-97-8	butane, pure	30-<35%
EINECS: 203-448-7	 Flam. Gas 1, H220	
Index number: 601-004-00-0	 Press. Gas C, H280	
RTECS: EJ 4200000	 Acute Tox. 3, H331	
	 Muta. 1A, H340; Carc. 1A, H350	
CAS: 123-86-4	n-butyl acetate	15-<20%
EINECS: 204-658-1	 Flam. Liq. 3, H226	
Index number: 607-025-00-1	 STOT SE 3, H336	
RTECS: AF 7350000	Acute Tox. 5, H333	
CAS: 1330-20-7	xylene	15-<20%
EINECS: 215-535-7	 Flam. Liq. 3, H226	
Index number: 601-022-00-9	 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	
RTECS: ZE 2100000	Acute Tox. 5, H303	
CAS: 471-34-1	calcium carbonate	5-<10%
EINECS: 207-439-9	substance with a Community workplace exposure limit	
RTECS: EV 9580000		
CAS: 13463-67-7	titanium dioxide	5-<10%
EINECS: 236-675-5	Acute Tox. 5, H333	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	2.5-<5%
EINECS: 203-603-9	 Flam. Liq. 3, H226	
Index number: 607-195-00-7	Acute Tox. 5, H333	
CAS: 75-28-5	isobutane	2.5-<5%
EINECS: 200-857-2	 Flam. Gas 1, H220	
Index number: 601-004-00-0	 Press. Gas C, H280	
RTECS: TZ 4300000	 Muta. 1A, H340; Carc. 1A, H350	
CAS: 67-64-1	acetone	2.5-<5%
EINECS: 200-662-2	 Flam. Liq. 2, H225	
Index number: 606-001-00-8	 Eye Irrit. 2A, H319; STOT SE 3, H336	
RTECS: AL 3150000		
CAS: 74-98-6	propane	2.5-<5%
EINECS: 200-827-9	 Flam. Gas 1, H220	
Index number: 601-003-00-5	 Press. Gas C, H280	
RTECS: TX 2275000		

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

NZ
(Contd. on page 4)

Trade name: BODY BUMPER PAINT SPRAY

(Contd. of page 3)

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Fire fighting measures**5.1 Extinguishing media**

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

Speial protective equipment and fire fighting procedures: No special measures required.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 5)

NZ

Trade name: **BODY BUMPER PAINT SPRAY**

(Contd. of page 4)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

* **SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
 - **Ingredients with limit values that require monitoring at the workplace:**
-

106-97-8 butane, pure

WES (New Zealand) Long-term value: 1900 mg/m³, 800 ppm

123-86-4 n-butyl acetate

WES (New Zealand) Short-term value: 950 mg/m³, 200 ppm
Long-term value: 713 mg/m³, 150 ppm

IOELV (EU) Short-term value: 723 mg/m³, 150 ppm
Long-term value: 241 mg/m³, 50 ppm

1330-20-7 xylene

WES (New Zealand) Long-term value: 217 mg/m³, 50 ppm

IOELV (EU) Short-term value: 442 mg/m³, 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin

471-34-1 calcium carbonate

WES (New Zealand) Long-term value: 10 mg/m³

108-65-6 2-methoxy-1-methylethyl acetate

IOELV (EU) Short-term value: 550 mg/m³, 100 ppm
Long-term value: 275 mg/m³, 50 ppm
Skin

67-64-1 acetone

WES (New Zealand) Short-term value: 2375 mg/m³, 1000 ppm
Long-term value: 1185 mg/m³, 500 ppm
bio

IOELV (EU) Long-term value: 1210 mg/m³, 500 ppm

74-98-6 propane

WES (New Zealand) Simple asphyxiant; may present an explosion hazard

- **Regulatory information**

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices
IOELV (EU): (EU) 2019/1831

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.

(Contd. on page 6)

NZ

Trade name: **BODY BUMPER PAINT SPRAY**

(Contd. of page 5)

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**

Safety glasses



Tightly sealed goggles

· **Body protection:** Protective work clothing

* SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· **General Information**

· **Appearance:**

Form: Aerosol
Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: -44.5 °C

· **Flash point:** < 0 °C

· **Flammability (solid, gas):** Not applicable.

· **Autoignition temperature:** 315 °C

· **Decomposition temperature:** Not determined.

(Contd. on page 7)

NZ

Trade name: **BODY BUMPER PAINT SPRAY**

(Contd. of page 6)

- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.
- **Explosion limits:**
 - **Lower:** 1.2 Vol %
 - **Upper:** 8.5 Vol %
- **Vapour pressure at 20 °C:** 2,100 hPa
- **Density at 20 °C:** 1.0013 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with water:** Fully miscible.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
 - **Dynamic:** Not determined.
 - **Kinematic:** Not determined.
- **Solvent content:**
 - **Organic solvents:** 74.1 %
 - **VOC (EC)** 778.3-778.4 g/l
 - **Solids content (volume):** 22.1 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
May be harmful if inhaled.
- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral LD50 28.482 mg/kg (rat)
Dermal LD50 13.247 mg/kg (rabbit)
Inhalative LC50/4 h >31.6 mg/l

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

(Contd. on page 8)

Trade name: BODY BUMPER PAINT SPRAY

(Contd. of page 7)

123-86-4 n-butyl acetate

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)
Inhalative LC50/4 h >21 mg/l (rat)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

471-34-1 calcium carbonate

Oral LD50 6,450 mg/kg (rat)

13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat)
Dermal LD50 >10,000 mg/kg (rabbit)
Inhalative LC50/4 h >6.82 mg/l (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)
Inhalative LC50/4 h 35.7 mg/l (rat)

67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)
Dermal LD50 20,000 mg/kg (rabbit)

· **Primary irritant effect:**

· **Skin corrosion/irritation**

Causes skin irritation.

· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

· **Germ cell mutagenicity**

May cause genetic defects.

· **Carcinogenicity**

May cause cancer.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure**

May cause drowsiness or dizziness.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· **12.2 Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

· **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 9)

Trade name: **BODY BUMPER PAINT SPRAY**

(Contd. of page 8)

- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **12.6 Other adverse effects** No further relevant information available.

* SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** UN1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**

· **ADR**



- **Class** 2.5F Gases.
- **Label** 2.1
- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1
- **14.4 Packing group**
- **ADR, IMDG, IATA** Void

- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Gases.

(Contd. on page 10)

Trade name: **BODY BUMPER PAINT SPRAY**

(Contd. of page 9)

· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW2 Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

* **SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

· **New Zealand Inventory of Chemicals**

- 106-97-8 butane, pure
- 123-86-4 n-butyl acetate
- 1330-20-7 xylene
- 9003-55-8 resin
- 471-34-1 calcium carbonate
- 13463-67-7 titanium dioxide
- 108-65-6 2-methoxy-1-methylethyl acetate
- 75-28-5 isobutane
- 67-64-1 acetone
- 74-98-6 propane
- 68609-36-9 modified chlorinated polyolefin
- 100-41-4 ethylbenzene
- 108-90-7 chlorobenzene
- 61789-01-3 epoxidised oil
- 1333-86-4 Carbon black
- 112945-52-5 aerosil 200

(Contd. on page 11)

NZ

Trade name: BODY BUMPER PAINT SPRAY

(Contd. of page 10)

1330-20-7 xylene
78-83-1 butanol

· **HSNO Approval numbers**

HSNO Number/HSNO Group Standard HSR002515
106-97-8 butane, pure: HSR000989
123-86-4 n-butyl acetate: HSR001091
1330-20-7 xylene: HSR000983
471-34-1 calcium carbonate: HSR006678
108-65-6 2-methoxy-1-methylethyl acetate: HSR001219
75-28-5 isobutane: HSR001003
67-64-1 acetone: HSR001070
74-98-6 propane: HSR001010

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labelling:**

butane, pure
xylene
isobutane

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H333 May be harmful if inhaled.
H315 Causes skin irritation.
H340 May cause genetic defects.
H350 May cause cancer.
H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P251 Pressurized container: Do not pierce or burn, even after use.
P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P3a FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 12)

Trade name: BODY BUMPER PAINT SPRAY

(Contd. of page 11)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H220 Extremely flammable gas.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H280 Contains gas under pressure; may explode if heated.
 H303 May be harmful if swallowed.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H333 May be harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H340 May cause genetic defects.
 H350 May cause cancer.

- **Department issuing SDS:** Department of Quality Control

- **Contact:**

HB BODY S.A
 Ms Olympia Stamkou
 Ph: +30 2310 790 032
 fax: +30 2310 790 033
 email: stamkou@hbbody.com

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1: Flammable gases – Category 1
 Aerosol 1: Aerosols – Category 1
 Press. Gas C: Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity - dermal – Category 4
 Acute Tox. 3: Acute toxicity - inhalation – Category 3
 Acute Tox. 5: Acute toxicity - inhalation – Category 5
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Muta. 1A: Germ cell mutagenicity – Category 1A
 Carc. 1A: Carcinogenicity – Category 1A
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 13)

NZ

Trade name: **BODY BUMPER PAINT SPRAY**

(Contd. of page 12)

· * **Data compared to the previous version altered.**

NZ
(Contd. on page 14)

Trade name: BODY BUMPER PAINT SPRAY

(Contd. of page 13)

Annex: Exposure scenario 1

- **Short title of the exposure scenario**
- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- **Article category** AC1 Vehicles
- **Environmental release category** ERC2 Formulation into mixture
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** According to directions for use.
- **Duration and frequency** Frequency of use:
- **Physical parameters**
The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.
- **Physical state** Aerosol
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
Avoid contact with the skin.
Do not breathe aerosol.
Take precautionary measures against static discharge.
Keep away from sources of ignition - No smoking.
Avoid contact with eyes.
- **Other operational conditions affecting consumer exposure**
No special measures required.
Keep out of the reach of children.
- **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures**
Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Avoid contact with the skin.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Pregnant women should strictly avoid inhalation or skin contact.
Avoid contact with the eyes.
Tightly sealed goggles
- **Measures for consumer protection**
Ensure adequate labelling.
Observe consumer information and advice on safe use.

(Contd. on page 15)

NZ

Trade name: BODY BUMPER PAINT SPRAY

(Contd. of page 14)

Keep locked up and out of the reach of children.

· Environmental protection measures

· **Water** Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· Exposure estimation

· **Consumer** This product is to be used by professional technicians only.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

NZ

(Contd. on page 16)

Trade name: BODY BUMPER PAINT SPRAY

(Contd. of page 15)

Annex: Exposure scenario 2**Short title of the exposure scenario**

- **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- **Conditions of use** According to directions for use.

- **Duration and frequency** Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- **Physical state** Fluid

- **Concentration of the substance in the mixture** Raw material.

- **Other operational conditions**

- **Other operational conditions affecting environmental exposure** No special measures required.

- **Other operational conditions affecting worker exposure**

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- **Other operational conditions affecting consumer exposure** Keep out of the reach of children.

- **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

Risk management measures**Worker protection****Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

No special measures required.

Provide explosion-proof electrical equipment.

Personal protective measures

Do not inhale gases / fumes / aerosols.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

Observe consumer information and advice on safe use.

Environmental protection measures

- **Water** Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

- **Soil** The product is only processed over the concrete collecting basin.

- **Disposal measures** Ensure that waste is collected and contained.

- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Waste type** Partially emptied and uncleaned packaging

Exposure estimation**Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

(Contd. on page 17)

NZ

Trade name: BODY BUMPER PAINT SPRAY

(Contd. of page 16)

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

NZ
(Contd. on page 18)

Trade name: BODY BUMPER PAINT SPRAY

(Contd. of page 17)

Annex: Exposure scenario 3**· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· Conditions of use According to directions for use.**· Duration and frequency** Frequency of use:**· Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· Physical state Fluid**· Concentration of the substance in the mixture** Raw material.**· Other operational conditions****· Other operational conditions affecting environmental exposure** No special measures required.**· Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· Other operational conditions affecting consumer exposure No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**· Risk management measures****· Worker protection****· Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· Environmental protection measures**· Water** Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.**· Soil** The product is only processed over the concrete collecting basin.**· Disposal measures** Ensure that waste is collected and contained.**· Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**· Waste type** Partially emptied and uncleaned packaging**· Exposure estimation****· Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

(Contd. on page 19)

NZ

Trade name: BODY BUMPER PAINT SPRAY

(Contd. of page 18)

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

NZ