



Auto Refinishing Products

Page 1/14

Printing date 24.04.2020

Revision: 24.04.2020

Version number 36

Safety Data Sheet  
in accordance with HSNO

## SECTION 1: Identification of the substance or mixture and of the supplier

### 1.1 Product identifier

Trade name: **BODY S115 AUTOSEAL SEAM SEALER**

Article number: 248

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category** PC8 Biocidal products

**Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

**Environmental release category** ERC2 Formulation into mixture

**Article category** AC1 Vehicles

### Application of the substance / the mixture

Sealer

Surface protection

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

#### Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

NZ  
(Contd. on page 2)

Trade name: **BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 1)

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Repr. 1A H360 May damage fertility or the unborn child.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Acute Tox. 5 H333 May be harmful if inhaled.

· **Additional information:**

6.1E Substances that are acutely toxic – May be harmful, aspiration hazard

6.3A Substances that are irritating to the skin

8.3A Substances that are corrosive to ocular tissue

6.4A Substances that are irritating to the eye

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02



GHS07



GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

toluene

2-butoxyethanol

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P405 Store locked up.

(Contd. on page 3)

NZ

**Trade name: BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 2)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards****Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/Information on ingredients****3.2 Chemical characterisation: Mixtures**• **Description:** Mixture of hazardous substances**Dangerous components:**

|                            |  |          |
|----------------------------|--|----------|
| CAS: 64742-49-0            | Naphtha (petroleum), hydrotreated light  | 15-<20%  |
| EINECS: 265-151-9          | Flam. Liq. 2, H225   |          |
| Index number: 649-328-00-1 | Asp. Tox. 1, H304  |          |
| CAS: 108-88-3              | toluene  | 5-<10%   |
| EINECS: 203-625-9          | Flam. Liq. 2, H225   |          |
| Index number: 601-021-00-3 | Repr. 1A, H360; STOT RE 2, H373; Asp. Tox. 1, H304   |          |
| RTECS: XS 5250000          | Skin Irrit. 2, H315  |          |
|                            | Acute Tox. 5, H303   |          |
| CAS: 123-86-4              | n-butyl acetate  | 5-<10%   |
| EINECS: 204-658-1          | Flam. Liq. 3, H226   |          |
| Index number: 607-025-00-1 | STOT SE 3, H336  |          |
| RTECS: AF 7350000          | Acute Tox. 5, H333   |          |
| CAS: 13463-67-7            | titanium dioxide   | 2.5-<5%  |
| EINECS: 236-675-5          | Acute Tox. 5, H333   |          |
| CAS: 111-76-2              | 2-butoxyethanol  | <2.5%    |
| EINECS: 203-905-0          | Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319 |          |
| Index number: 603-014-00-0 | Flam. Liq. 4, H227   |          |
| RTECS: KJ 8575000          |  |          |
| CAS: 71-36-3               | butan-1-ol   | ≥1-<2.5% |
| EINECS: 200-751-6          | Flam. Liq. 3, H226   |          |
| Index number: 603-004-00-6 | Eye Dam. 1, H318   |          |
| RTECS: EO 1400000          | Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336  |          |
|                            | Acute Tox. 5, H313   |          |

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.• **After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

• **After swallowing:** If symptoms persist consult doctor.• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

NZ

**Trade name: BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 3)

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Fire fighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**5.3 Advice for firefighters**

Firefighters should always use protective equipment and breathing apparatus when handling fire coming from these products

**Special protective equipment and fire fighting procedures:** No special measures required.**Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

HAZ CHEM CODE: 3YE

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling** Open and handle receptacle with care.**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** Store in a cool location.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

**7.3 Specific end use(s)** No further relevant information available.NZ  
(Contd. on page 5)

Trade name: **BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 4)

**SECTION 8: Exposure controls/personal protection**

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**108-88-3 toluene**

WES (New Zealand) Long-term value: 188 mg/m<sup>3</sup>, 50 ppm  
skin

IOELV (EU) Short-term value: 384 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 192 mg/m<sup>3</sup>, 50 ppm  
Skin

**123-86-4 n-butyl acetate**

WES (New Zealand) Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

IOELV (EU) Short-term value: 723 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 241 mg/m<sup>3</sup>, 50 ppm

**111-76-2 2-butoxyethanol**

WES (New Zealand) Long-term value: 121 mg/m<sup>3</sup>, 25 ppm  
skin

IOELV (EU) Short-term value: 246 mg/m<sup>3</sup>, 50 ppm  
Long-term value: 98 mg/m<sup>3</sup>, 20 ppm  
Skin

**71-36-3 butan-1-ol**

WES (New Zealand) Ceiling limit: 150 mg/m<sup>3</sup>, 50 ppm  
skin

· **Regulatory information**

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

NZ

Trade name: **BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Fluid  
**Colour:** According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/freezing point:** Undetermined.

**Initial boiling point and boiling range:** 36 °C

· **Flash point:** < 0 °C

· **Flammability (solid, gas):** Not applicable.

· **Autoignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.

· **Explosion limits:**

**Lower:** 1.2 Vol %

**Upper:** 7 Vol %

· **Vapour pressure at 20 °C:** 3.5 hPa

· **Density at 20 °C:** 1.08 g/cm<sup>3</sup>

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

**water:** Fully miscible.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

**Dynamic:** Not determined.

(Contd. on page 7)

Trade name: **BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 6)

|                                 |  |
|---------------------------------|--|
| <b>Kinematic:</b>               | Not determined.                            |
| <b>Solvent content:</b>         |  |
| <b>Organic solvents:</b>        | 36.2 %                                     |
| <b>VOC (EC)</b>                 | 290.0 g/l                                  |
| <b>Solids content (volume):</b> | 50.3 %                                     |
| <b>9.2 Other information</b>    | No further relevant information available. |

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Acute toxicity**

May be harmful if inhaled.

**LD/LC50 values relevant for classification:**

**ATE (Acute Toxicity Estimates)**

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | 18,211 mg/kg (rat) |
| Dermal     | LD50     | 17,945 mg/kg       |
| Inhalative | LC50/4 h | >102 mg/l          |

**108-88-3 toluene**

|            |               |                       |
|------------|---------------|-----------------------|
| Oral       | LD50          | 5,000 mg/kg (rat)     |
| Dermal     | LD50 (static) | 12,124 mg/kg (rabbit) |
| Inhalative | LC50/4 h      | 5,320 mg/l (mouse)    |

**123-86-4 n-butyl acetate**

|            |          |                       |
|------------|----------|-----------------------|
| Oral       | LD50     | 13,100 mg/kg (rat)    |
| Dermal     | LD50     | >5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >21 mg/l (rat)        |

**13463-67-7 titanium dioxide**

|            |          |                        |
|------------|----------|------------------------|
| Oral       | LD50     | >20,000 mg/kg (rat)    |
| Dermal     | LD50     | >10,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >6.82 mg/l (rat)       |

**111-76-2 2-butoxyethanol**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 1,480 mg/kg (rat) |
| Dermal     | LD50     | 400 mg/kg (rab)   |
| Inhalative | LC50/4 h | 11 mg/l (ATE)     |

**71-36-3 butan-1-ol**

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 790 mg/kg (rat)      |
| Dermal | LD50 | 3,400 mg/kg (rabbit) |

(Contd. on page 8)

**Trade name: BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 7)

Inhalative LC50/4 h 8,000 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
May damage fertility or the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

- **12.1 Toxicity**
- **Aquatic toxicity:**  
This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea
- **12.2 Persistence and degradability**  
This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

NZ  
(Contd. on page 9)



Trade name: **BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 8)

**SECTION 14: Transport information**

· 14.1 UN-Number

· **ADR, IMDG, IATA**

UN1263

· 14.2 UN proper shipping name

· **ADR**

UN1263 PAINT, special provision 640D

· **IMDG, IATA**

PAINT

· 14.3 Transport hazard class(es)

· **ADR**



· **Class**

3 (F1) Flammable liquids.

· **Label**

3

· **IMDG, IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· 14.4 Packing group

· **ADR, IMDG, IATA**

II

· 14.5 Environmental hazards:

· **Marine pollutant:**

No

· 14.6 Special precautions for user

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):**

33

· **EMS Number:**

F-E,S-E

· **Stowage Category**

B

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category**

2

· **Tunnel restriction code**

D/E

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **IATA**

· **Remarks:**

HAZ CHEM CODE: 3YE

(Contd. on page 10)

NZ

Trade name: **BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 9)

· **UN "Model Regulation":**

UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

**SECTION 15: Regulatory information**

·3YE

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

· **New Zealand Inventory of Chemicals**

All ingredients are listed.

· **HSNO Approval numbers**

HSNO Approval number HSR 002662

Group standard name Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Hazard classification Refer to section 2

108-88-3 toluene: HSR001227

123-86-4 n-butyl acetate: HSR001091

111-76-2 2-butoxyethanol: HSR001154

71-36-3 butan-1-ol: HSR001096

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

toluene

2-butoxyethanol

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 11)

NZ

**Trade name: BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 10)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H227 Combustible liquid.  
 H302 Harmful if swallowed.  
 H303 May be harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H313 May be harmful in contact with skin.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H333 May be harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H360 May damage fertility or the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.

- **Department issuing SDS:** Department of Quality Control

- **Contact:**

HB BODY S.A  
 Ms Olympia Stamkou  
 Ph: +30 2310 790 032  
 fax: +30 2310 790 033  
 email: stamkou@hbbody.com

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
 ICAO: International Civil Aviation Organisation  
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Flam. Liq. 4: Flammable liquids – Category 4  
 Acute Tox. 4: Acute toxicity - oral – Category 4  
 Acute Tox. 5: Acute toxicity - oral – Category 5  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
 Repr. 1A: Reproductive toxicity – Category 1A

(Contd. on page 12)

NZ

**Trade name: BODY S115 AUTOSEAL SEAM SEALER**

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. of page 11)

NZ  
(Contd. on page 13)

**Trade name: BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 12)

**Annex: Exposure scenario****· Short title of the exposure scenario****· Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)**· Product category** PC8 Biocidal products**· Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities**· Article category** AC1 Vehicles**· Environmental release category** ERC2 Formulation into mixture**· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**· Conditions of use** According to directions for use.**· Duration and frequency** Frequency of use:**· Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**· Physical state** Fluid**· Concentration of the substance in the mixture** The substance is main component.**· Used amount per time or activity** Smaller than 100 g per application.**· Other operational conditions****· Other operational conditions affecting environmental exposure**

No special measures required.

Use only on hard ground.

**· Other operational conditions affecting worker exposure**

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with the skin.

Avoid contact with eyes.

**· Other operational conditions affecting consumer exposure** No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**· Risk management measures****· Worker protection****· Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

**· Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

**· Personal protective measures**

Do not inhale gases / fumes / aerosols.

Pregnant women should strictly avoid inhalation or skin contact.

Avoid contact with the skin.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Avoid contact with the eyes.

Tightly sealed goggles

**· Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

(Contd. on page 14)

NZ

**Trade name: BODY S115 AUTOSEAL SEAM SEALER**

(Contd. of page 13)

**· Environmental protection measures****· Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.  
Do not allow to reach sewage system.

**· Soil**

The product is only processed over the concrete collecting basin.  
Prevent contamination of soil.

**· Disposal measures** Ensure that waste is collected and contained.**· Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**· Waste type** Partially emptied and uncleaned packaging**· Exposure estimation****· Consumer** This product is to be used by professional technicians only.**· Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

NZ